



C76

UHF RFID Reader



Android



4G



WiFi



Bluetooth



UHF



1D Barcode



2D Barcode



IRIS



NFC



Camera



GPS

Chainway C76, based on Android 6.0 operating system, is newly developed to be much lighter than previous UHF RFID readers. It features powerful quad-core processor, 6600mAh battery, distant UHF RFID capability, NFC, barcode scanning, and iris recognition. This rugged device can be deployed in chain stores, retail inventory management, asset management, warehousing, fleet management, ETC, and finance.



Specification

Physical Characteristics

| | |
|-----------------------|--|
| Dimensions | 162.5*80.0*14.5mm/6.40*3.15*0.57in |
| Weight | 540g/19.0oz |
| Display | 5.2" IPS FHD 1920x1080 |
| Touch Panel | Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported |
| Power | Main battery: Li-ion, rechargeable, 4000mAh Pistol battery: Li-ion, 2600mAh Standby: over 400 hours Continuous use: over 12 hours (depending on user environment) Charging time: 3-4 hours (with standard adaptor and USB cable) |
| Expansion Slot | 1 slot for SIM card, 1 slot for SIM or TF card |
| Interfaces | USB2.0 Type-C, OTG |
| Audio | Speaker, microphone |
| Keypad | 4 front keys, 1 power key, 2 scan keys, 1 multifunctional key |
| Sensors | Gravity sensor, light sensor, proximity sensor |

Performance

| | |
|------------------|------------------------------------|
| CPU | Cortex-A53 Quad-core 1.3GHz |
| RAM+ROM | 2GB+16GB |
| Expansion | Supports up to 32 GB Micro SD card |

Developing Environment

| | |
|-------------------------|-----------------------------------|
| Operating System | Android 6.0 |
| SDK | Chainway Software Development Kit |
| Language | Java |
| Tool | Eclipse / Android Studio |

User Environment

| | |
|-----------------------------|--|
| Operating Temp. | -4°F to 122°F / -20°C to 50°C |
| Storage Temp. | -40°F to 158°F / -40°C to 70°C |
| Humidity | 5%RH - 95%RH non condensing |
| Drop Specification | Multiple 1.5m/4.9ft drops (at least 20 times) to the concrete across the operating temperature range |
| Tumble Specification | 1000 x 0.5m/1.6ft falls at room temperature |
| Sealing | Host IP65 per IEC sealing specifications |
| ESD | ±8KV air discharge, ±4KV conductive discharge |

Communication

| | |
|-------------|---|
| WLAN | IEEE802.11 a/b/g/n, 2.4G/5G dual-band, internal antenna |
|-------------|---|

| | |
|---------------------|--|
| WWAN (China) | 2G: 900/1800MHz |
| | 3G: 900/1900/2000/2100MHz |
| | 4G: TDD-LTE: B38, B39, B40, B41 FDD-LTE: B1, B3, B5 |
| Bluetooth | Bluetooth 4.0, BLE |
| GNSS | GPS/AGPS, GLONASS, BeiDou; internal antenna |

Data Collection

Camera

| | |
|-------------------|---------------------------|
| Top Camera | 13MP Autofocus with flash |
|-------------------|---------------------------|

RFID

UHF

| | |
|---------------------|---|
| Frequency | 865MHz-868MHz / 920-925MHz / 902-928MHz |
| Protocol | EPC C1 GEN2 / ISO18000-6C |
| Antenna | Circular polarization (3dBi) |
| Power | 1W (30dBm, +5dBm to +30dBm adjustable) |
| R/W range | >22m (indoors); >8m (open outdoors) |
| Reading rate | >200 tags/s |

* Ranges and rates depend on tags and environment

NFC (Optional)

| | |
|------------------|----------|
| Frequency | 13.56MHz |
|------------------|----------|

Barcode Scanning (Optional)

| | |
|--------------------------|---|
| 2D Imager Scanner | Honeywell N6603 |
| 1D Symbologies | UPC/EAN, Code128, Code39, Code93, Code11, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, MSI, RSS, etc. |
| 2D Symbologies | PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc. |

Front Iris (optional)

| | |
|-----------------|----------------------------------|
| Rate | <150ms |
| Range | 20-40cm |
| FAR | 1/10000000 |
| Protocol | ISO/IEC 19794-6, GB/T 20979-2007 |

Accessories(See details in Accessory Guide)



AC Adaptor



USB Cable

Notice: Product specifications are subject to change without prior notice. / Model: C76 / Update Date: 2018-08-30

CHAINWAY[®]

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: http://www.chainway.net