

**TCB****GRANT OF EQUIPMENT  
AUTHORIZATION****TCB****Certification****Issued Under the Authority of the  
Federal Communications Commission****By:**Telefication B.V.  
Edisonstraat 12a  
Zevenaar, NL-6902 PK  
Netherlands

Date of Grant: 01/09/2018

Application Dated: 01/05/2018

**Shenzhen Chainway Information Technology Co.,  
Ltd.****9/F, Building 2, Daqian Industrial Park,  
Longchang Rd., District 67, Bao'an,  
Shenzhen,  
China****Attention: Li Wenzhang , Manager****NOT TRANSFERABLE**EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE,  
and is VALID ONLY for the equipment identified hereon for use under the  
Commission's Rules and Regulations listed below.**FCC IDENTIFIER:** 2AC6AC70  
**Name of Grantee:** Shenzhen Chainway Information  
Technology Co., Ltd.  
**Equipment Class:** PCS Licensed Transmitter held to ear  
**Notes:** Mobile Data Terminal

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	22H	824.2 - 848.8	1.256	0.1124 PM	246KGXW
	22H	824.2 - 848.8	0.436	0.116 PM	246KG7W
	22H	826.4 - 846.6	0.171	0.0527 PM	4M24F9W
	24E	1850.2 - 1909.8	0.656	0.0505 PM	246KGXW
	24E	1850.2 - 1909.8	0.33	0.0521 PM	246KG7W
	24E	1852.4 - 1907.6	0.102	0.1136 PM	4M23F9W
	27	1712.4 - 1752.6	0.124	0.0473 PM	4M22F9W
	24E	1850.7 - 1909.3	0.176	0.0468 PM	18M0G7D
	24E	1850.7 - 1909.3	0.173	0.0468 PM	18M0W7D
	24E	1850.7 - 1909.3	0.168	0.0468 PM	13M5G7D
	24E	1850.7 - 1909.3	0.176	0.0468 PM	13M5W7D
	27	1710.7 - 1754.3	0.202	0.0566 PM	18M0G7D
	27	1710.7 - 1754.3	0.177	0.0566 PM	18M0W7D
	27	1710.7 - 1754.3	0.196	0.0566 PM	13M5G7D
	27	1710.7 - 1754.3	0.184	0.0566 PM	1M10W7D
	27	2502.5 - 2567.5	0.132	0.0347 PM	18M0G7D
	27	2502.5 - 2567.5	0.132	0.0347 PM	18M0W7D

<b>27</b>	<b>2502.5 - 2567.5</b>	<b>0.15</b>	<b>0.0347 PM</b>	<b>4M53G7D</b>
<b>27</b>	<b>2502.5 - 2567.5</b>	<b>0.129</b>	<b>0.0347 PM</b>	<b>13M5W7D</b>
<b>27</b>	<b>699.7 - 715.3</b>	<b>0.159</b>	<b>0.1343 PM</b>	<b>9M08G7D</b>
<b>27</b>	<b>699.7 - 715.3</b>	<b>0.136</b>	<b>0.1343 PM</b>	<b>9M07W7D</b>
<b>27</b>	<b>699.7 - 715.3</b>	<b>0.157</b>	<b>0.1343 PM</b>	<b>1M10G7D</b>
<b>27</b>	<b>699.7 - 715.3</b>	<b>0.136</b>	<b>0.1343 PM</b>	<b>4M57W7D</b>
<b>27</b>	<b>706.5 - 713.5</b>	<b>0.128</b>	<b>0.131 PM</b>	<b>9M05G7D</b>
<b>27</b>	<b>706.5 - 713.5</b>	<b>0.119</b>	<b>0.131 PM</b>	<b>9M05W7D</b>
<b>27</b>	<b>706.5 - 713.5</b>	<b>0.127</b>	<b>0.131 PM</b>	<b>4M53G7D</b>
<b>27</b>	<b>706.5 - 713.5</b>	<b>0.119</b>	<b>0.131 PM</b>	<b>4M55W7D</b>

Output power is ERP for Part 22 and 27(Below 1 GHz) and EIRP for Part 24 and 27(Above 1 GHz). SAR compliance for body-worn operating conditions is limited to the specific configuration tested for this filing. Body-worn operations are restricted to belt-clips, holsters or similar accessories that have no metallic component in the assembly and must provide at least 10 mm separation between the device and the user's body, which includes use as hotspot. End users must be informed of the body worn requirements for satisfying RF Exposure compliance.

The highest reported SAR values for head, body-worn accessory, product specific (wireless router), and simultaneous transmission use conditions are 0.14 W/kg, 0.79 W/kg, 0.79 W/kg, and 1.32 W/kg, respectively.

