

# **Test Report**

This report is to supersede test report ET201709003

Name of Sample:	MOBILE DATA TERMINAL				
Model No.:	C70				
Brand Name:	CHAINWAY				
Client:	SHENZHEN CHAINWAY INFORMATION TECHNOLOGY CO				
	LTD.				
Manufacturer:	SHENZHEN CHAINWAY INFORMATION TECHNOLOGY CO.,				
	LTD.				
Test Sort:	Commission Test				
Test Item:	Dust-proof and Water-proof Test				

# Shenzhen EBO Technology Co., Ltd.

Address: A112~114, Qinye Business Center, Xin'an Sixth Road, 82<sup>th</sup> District, Bao'an, Shenzhen, China.

TEL: 0755-29451282

FAX: 0755-22639141

Web: http://www.ebotek.cn

E-Mail: ebo@ebotek.cn

TRF No.: IEC 60529 Rev.0 Page 1 of 7



Shenzhen EBO Technology Co., Ltd.							
Test Report							
Client	SHENZHEN CHAINWAY INFORMATION TECHNOLOGY CO., LTD.						
Address	9/F, Building 2, Daqian Industrial Park, Longchang Rd., District 67, Bao'an, Shenzhen.						
Manufacturer	SHENZHEN CHAINWAY INFORMATION TECHNOLOGY CO., LTD.						
Name of sample	MOBILE DATA TERMINAL						
Brand Name	CHAINWAY	Model No.	C70				
Sample size	1	Samples Weight	1				
Application date	September 1, 2017	Test date	September 1, 2017 to September 5, 2017				

#### Sample description:

1PCS, in good condition before test. Number: 1#

#### Test item:

Dust-proof Test and Water-proof Test (IP67)

#### Reference documents:

According to client's test specification.

Test Method Reference to IEC 60529:2013

#### Test Results:

See next page for test results.

EBO
Date: September 29 2017

Tested by:

Reviewed & Approved by:

Don wang

(General Manager)

Rep No. ET201709003A



### **Test Equipment:**

Name	Туре	Serial No.	Calibration useful-life
Dust tester	WH-SC800	E00134	September 7, 2018
Leaching tank	IPX7	E00152	September 7, 2018

#### Lab Environmental Conditions:

Ambient temperature:  $25^{\circ}C \pm 3^{\circ}C$ Relative humidity:  $55\% \pm 2\%$ RH

# **Test Method/ Specification:**

Test method: Reference to IEC 60529—IP67

1. Test for protection against solid foreign objects:

Sample condition: Non-Operating

Type of dust: Talcum powder Maximum pressure: 2kpa

Test duration: 8 hours

• Examine the protection against ingress dust of specimen after this test.

#### 1. Test for protection against water:

Sample condition: Non-Operating

Test means: completely immerse the specimen in water in its service position as specified by client the lowest point of enclosures with a height less than 850mm is located 1000mm below the surface of the water.

• Examine the protection against ingress water of specimen after this test.

TRF No.: IEC 60529 Rev.0



## **Test Results:**

Check Item Test Item	Visual check
IP6X	No trace of dust inside
IPX7	No ingress of water was found inside

TRF No.: IEC 60529 Rev.0




#### Before test Photo




**Test Photos** 





IPX7





IPX7

Blank



#### After test Photos







IPX7 Visua check

TRF No.: IEC 60529 Rev.0 Page 6 of 7



# **Statement**

- 1. The report is just responsible for the tested sample.
- 2. The test report is invalid without stamp of laboratory.
- 3. The test report is invalid without signature of person(s) testing and authorizing.
- 4. The test report is invalid if erased and corrected.
- Test results of the report is valid to the test samples if sampling by client.
- 6. The test report shall not be reproduced except in full, without written approval of the laboratory.
- 7. The test report shall not be published as advertisement without the written approval of EBOTEK.
- 8. If there is any objection to report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

TRF No.: IEC 60529 Rev.0