



C76

UHF RFID Reader



Chainway C76, based on Android 6.0 operating system, is newly developed to be much lighter than previous UHF RFID readers. It features powerful quad-core processor, 6600mAh battery, distant UHF RFID capability, NFC, barcode scanning, and iris recognition. This rugged device can be deployed in chain stores, retail inventory management, asset management, warehousing, fleet management, ETC, and finance.



Specification

Physical Characteristics

Dimensions	162.5*80.0*14.5mm/6.40*3.15*0.57in
Weight	540g/19.0oz
Display	5.2" IPS FHD 1920x1080
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Power	Main battery: Li-ion, rechargeable, 4000mAh Pistol battery: Li-ion, 2600mAh Standby: over 400 hours Continuous use: over 12 hours (depending on user environment) Charging time: 3-4 hours (with standard adaptor and USB cable)
Expansion Slot	1 slot for SIM card, 1 slot for SIM or TF card
Interfaces	USB2.0 Type-C, OTG
Audio	Speaker, microphone
Keypad	4 front keys, 1 power key, 2 scan keys, 1 multifunctional key
Sensors	Gravity sensor, light sensor, proximity sensor

Performance

CPU	Cortex-A53 Quad-core 1.45GHz
RAM+ROM	2GB+16GB
Expansion	Supports up to 128 GB Micro SD card

Developing Environment

Operating System	Android 6.0
SDK	Chainway Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

User Environment

Operating Temp.	-4°F to 122°F / -20°C to 50°C
Storage Temp.	-40°F to 158°F / -40°C to 70°C
Humidity	5%RH - 95%RH non condensing
Drop Specification	Multiple 1.5m/4.9ft drops (at least 20 times) to the concrete across the operating temperature range
Tumble Specification	1000 x 0.5m/1.6ft falls at room temperature
Sealing	Host IP65 per IEC sealing specifications
ESD	±15KV air discharge, ±6KV conductive discharge

Communication

WLAN	IEEE802.11 a/b/g/n, 2.4G/5G dual-band, internal antenna
-------------	---

WWAN (China)	2G: 900/1800MHz
	3G: 900/1900/2000/2100MHz
	4G: TDD-LTE: B38, B39, B40, B41 FDD-LTE: B1, B3, B5
Bluetooth	Bluetooth 4.0, BLE
GNSS	GPS/AGPS, GLONASS, BeiDou; internal antenna

Data Collection

Camera

Top Camera	13MP Autofocus with flash
-------------------	---------------------------

RFID

UHF

Frequency	865MHz-868MHz / 920-925MHz / 902-928MHz
Protocol	EPC C1 GEN2 / ISO18000-6C
Antenna	Circular polarization (3dBi)
Power	1W (30dBm, +5dBm to +30dBm adjustable)
R/W range	>22m (indoors); >8m (open outdoors)
Reading rate	>200 tags/s

* Ranges and rates depend on tags and environment

NFC (Optional)

Frequency	13.56MHz
------------------	----------

Barcode Scanning (Optional)

2D Imager Scanner	Honeywell N6603
1D Symbolologies	UPC/EAN, Code128, Code39, Code93, Code11, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, MSI, RSS, etc.
2D Symbolologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.

Front Iris (optional)

Rate	<150ms
Range	20-40cm
FAR	1/10000000
Protocol	ISO/IEC 19794-6, GB/T 20979-2007

Accessories(See details in Accessory Guide)



AC Adaptor



USB Cable

Notice: Product specifications are subject to change without prior notice. / Model: C76 / Update Date: 2018-10-18

CHAINWAY[®]

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: http://www.chainway.net