




P80

Industrial Tablet



Chainway P80 with abundant functions is an Android 7.1 rugged tablet. With its powerful Qualcomm CPU, 8 inch high-definition screen, 8000 mAh battery and comprehensive data capture options like UHF RFID, barcode scanning, HF RFID/ NFC, Iris and fingerprint recognition, etc., you can find this easy-to-deploy device a valuable helper to increase productivity in retail, logistics, warehousing, identity verification, meter reading, etc.



Specification

Physical Characteristics

Dimensions	250.8mm x 152mm x 15mm/ 9.87 x 5.98 x 0.59in(for standard version)
Weight	700g/24.7oz(for standard version)
Display	8" IPS LTPS 1920x1200
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Power	Main battery: Li-ion, rechargeable, 8000mAh Standby: over 500 hours Continuous use: over 10 hours (depending on user environment) Charging time: 5-7 hours (with standard AC adaptor and USB cable)
Expansion Slot	1 slot for SIM card, 1 slot for TF card, Optional PSAM card slot
Interfaces	USB 3.0 Type-C, OTG
Audio	Speaker, microphone
Keypad	1 front key, 1 volume key, 1 power key
Sensors	Gravity sensor

Performance

CPU	SDM450 1.8GHz Octa-core, MSM8953 2.0GHz Octa-core
RAM+ROM	2GB+16GB/3GB+32GB
Expansion	Supports up to 128GB Micro SD card

Developing Environment

Operating System	Android 7.1
SDK	Chainway Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

User Environment

Operating Temp.	-4°F to 122°F / -20°C to 50°C
Storage Temp.	-40°F to 158°F / -40°C to 70°C
Humidity	5%RH - 95%RH non condensing
Drop Specification	Multiple 1.5m/4.9ft drops to concrete across the operating temperature range
Tumble Specification	500 x 0.5m/1.64ft falls at room temperature
Sealing	IP65 per IEC sealing specifications
ESD	±15KV air discharge, ±8KV conductive discharge

Communication

WLAN	IEEE802.11 a/b/g/n/ac, 2.4G/5G dual-band, internal antenna 2G: 850/900/1800/1900MHz, GPRS, EDGE 3G: CDMA EVDO.B/C TD-SCDMA: B34/B39 WCDMA: B1/B2/B5/B8 4G: TDD-LTE: B38/B39/B40/B41 FDD-LTE: B1/B2/B3/B4/B5/B7/B8/B20/B26/B28
WWAN	
WWAN (Others)	Depending on the country's ISP
Bluetooth	Bluetooth 4.2/4.1+HS/4.0/3.0+HS/2.1+EDR
GNSS	GPS/AGPS, GLONASS, BeiDou, internal antenna

Data Collection

Camera

Rear Camera	13MP Autofocus with flash
Front Camera	8MP

Barcode Scanning (Optional)

Scan Engine	Zebra SE4710 (standard), Zebra SE4850 (optional)
1D Symbolgies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Symbolgies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch, Postal (KIX), etc.

RFID (Optional)

UHF

Frequency	865MHz-868MHz / 920-925MHz / 902-928MHz
Protocol	EPC C1 GEN2 / ISO18000-6C
Antenna	circular polarization (4dBi)
Power	1W (30dBm, +5dBm to +30dBm adjustable)
R/W range	> 10m (open outdoors); > 25m (indoors)
Reading rate	>200 tags/s

* Ranges and rates depend on tags and environment

NFC/HF(Optional)

Frequency	13.56MHz
------------------	----------

Fingerprint (Optional)

Option 1

Sensor	TCSI/TCS2 Capacitive
Sensing Area (mm)	12.8x18; 10.4x14.4
Resolution (dpi)	508 dpi, 8-bit greylevel
Certifications	FIPS 201, STQC
Format Extraction	ISO 19794, WSQ, ANSI 378, JPEG2000
Fake Finger Detection	Support by SDK
Security	AES, DES key encryption of the host communication channel

Option 2

Sensor	Optical Morpho CBM-E3
Sensing Area (mm)	14x22
Resolution (dpi)	500 dpi, 256 greylevel
Certifications	FIPS PIV IQS / ISO 19794-4, MINEX & FIPS 201 complaint, STQC
Format Extraction	ISO 19794-2/4, WSQ, ANSI 378, etc.
Fake Finger Detection	Latex, Gelatin, Plasticine, Kapton, Transparent Film, Silicone, Rubber, Play-doh, Graphite Or Paper
Security	FIPS 140-2 level 2, multiple security methods available, including image and templates encryption, template signature, secure tunneling, etc.

InfraRed (Reserved)

Wavelength	940nm
Frequency	38kHz
Range	> 4m
Protocol	DLT_645-2007, DLT_645-1997

Front Iris (Reserved)

Rate	<150ms
Range	20-40cm
FAR	1/10000000
Protocol	ISO/IEC 19794-6, GB/T 20979-2007

PSAM (Optional)

Card slot	2 PSAM card slot
Protocol	ISO7816

Accessories(See details in Accessory Guide)



AC Adaptor



USB Cable



Pistol



Wristband

Notice: Product specifications are subject to change without prior notice. / Model: P80 / Update Date: 2018-10-17

CHAINWAY®

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: http://www.chainway.net